

Postal Rate Chart Effective January 21, 2018

For more detailed pricing information, go to www.usps.com/business/prices.htm.
Find a transit time map at https://ribbs.usps.gov/modernservicestandards/ssmaps/find_map.cfm.



www.knightprinting.com • 701.235.1121 • 888.526.1121

FIRST CLASS MAIL (1-3 days standard transit time from 58103 in the Continental US)

	POSTCARDS	LETTERS	FLATS
Metered			
	0.35	0.47	
Non-Automation (under 1 oz)			
Single Piece (Machinable)	0.35	0.50	1.00
Presorted (Machinable)	0.280	0.458	0.799
Automation			
	0.257 - 0.274	0.378 - 0.424	0.474 - 0.705

STANDARD MAIL (3-8 days standard transit time from 58103 in the Continental US)

	LETTERS (3.5 oz. or less)		FLATS (4.0 oz. or less)	
	Standard	Non-Profit	Standard	Non-Profit
Non-Automation (Machinable)				
	0.256 - 0.300	0.141 - 0.185	0.413 - 0.634	0.247 - 0.468
Automation				
	0.220 - 0.287	0.105 - 0.172	0.340 - 0.598	0.174 - 0.432
Enhanced Carrier Route				
	0.158 - 0.292	0.083 - 0.210	0.156 - 0.295	0.073 - 0.213
Carrier Route EDDM (Saturation)				
	None - 0.186	None - 0.111	None - 0.219	None - 0.136
	NDC - 0.164	NDC - 0.089	NDC - 0.179	NDC - 0.096
	SCF - 0.158	SCF - 0.083	SLF - 0.165	SLF - 0.082
			DDU - 0.156	DDU - 0.073

EDDM Retail

Flats up to 3.3 oz. - 0.178

NOTES

- Minimum of 200 pieces to use an indicia.
- Minimum of 500 pieces for First Class automated rates.
- Minimum of 200 for Standard automated rates.
- Rectangle shape with aspect ratio (length divided by height) between 1.3 and 2.5.

MAILING PAPER STANDARDS

	MINIMUM	MAXIMUM
Postcard		
Height	3.5"	4.25"
Length	5"	6"
Thickness	0.0070"	0.0160"
Letters		
Height	3.5"	6.125"
Length	5"	11.5"
Thickness	0.0090"	0.25"
Folded Self Mailers		
Height	3.5"	6"
Length	5"	10.5"
Thickness	0.0090"	0.25"
# of Panels (counting both sides)	2	12
Flats		
Height	5"	12"
Length	6"	15"
Thickness	0.0090"	0.75"

Address Block Area for Letters

Minimum inkjet area needed 3.75" L x 1.5" H
Address block needs to be 0.625" from bottom of mail piece.

Address Block for Flats

Address Block needs to be on top half of mail piece with bound edge to the right and 1/8" clearance on all sides.

Postal Rate Chart Effective January 21, 2018

For more detailed pricing information, go to www.usps.com/business/prices.htm.
Find a transit time map at https://ribbs.usps.gov/modernservicestandards/ssmaps/find_map.cfm.

FIRST CLASS MAIL (1-3 days standard transit time from 58103 in the Continental US)				
	POSTCARDS	LETTERS	FLATS	
Metered				
	0.35	0.47		
Non-Automation (under 1 oz)				
Single Piece	(Machinable) 0.35	0.50	1.00	
Presorted	(Machinable) 0.280	0.458	0.799	
Automation				
	0.257 - 0.274	0.378 - 0.424	0.474 - 0.705	
STANDARD MAIL (3-8 days standard transit time from 58103 in the Continental US)				
	LETTERS (3.5 oz. or less)		FLATS (4.0 oz. or less)	
	Non-Automation (Machinable) Standard	Non-Profit	Standard	Non-Profit
	0.256 - 0.300	0.141 - 0.185	0.413 - 0.634	0.247 - 0.468
Automation				
	0.220 - 0.287	0.105 - 0.172	0.340 - 0.598	0.174 - 0.432
Enhanced Carrier Route				
	0.158 - 0.292	0.083 - 0.210	0.156 - 0.295	0.073 - 0.213
Carrier Route EDDM (Saturation)				
	None - 0.186	None - 0.111	None - 0.219	None - 0.136
	NDC - 0.164	NDC - 0.089	NDC - 0.179	NDC - 0.096
	SCF - 0.158	SCF - 0.083	SLF - 0.165	SLF - 0.082
			DDU - 0.156	DDU - 0.073
EDDM Retail				
			Flats up to 3.3 oz. - 0.178	

- NOTES**
- Minimum of 200 pieces to use an indicia.
 - Minimum of 500 pieces for First Class automated rates.
 - Minimum of 200 for Standard automated rates.
 - Rectangle shape with aspect ratio (length divided by height) between 1.3 and 2.5.



www.imageprinting.com • 701.222.4000

MAILING PAPER STANDARDS

	MINIMUM	MAXIMUM
Postcard		
Height	3.5"	4.25"
Length	5"	6"
Thickness	0.0070"	0.0160"
Letters		
Height	3.5"	6.125"
Length	5"	11.5"
Thickness	0.0090"	0.25"
Folded Self Mailers		
Height	3.5"	6"
Length	5"	10.5"
Thickness	0.0090"	0.25"
# of Panels (counting both sides)	2	12
Flats		
Height	5"	12"
Length	6"	15"
Thickness	0.0090"	0.75"

Address Block Area for Letters

Minimum inkjet area needed 3.75" L x 1.5" H
Address block needs to be 0.625" from bottom of mail piece.

Address Block for Flats

Address Block needs to be on top half of mail piece with bound edge to the right and 1/8" clearance on all sides.